

PRODUCT

Collections	Vertu • InGrained • Fused • HardCore • Sensatia	
Construction	Solid vinyl plank and tile; cross-ply, multi-layer backing system for optimal stability Phthalate-free*	
International Specifications	ASTM F 1700, Class III, Type B – embossed surface	
Product Thickness	3mm (0.120 in.)	
Wear Layer Thickness	20 mil (0.020 in.)	
Finish	Polyurethane protective coating	
Adhesive	Parterre Universal, #539, Royal Epoxy	
Maintenance Options	Polish • No Polish – Spray Buff/No Buff	
Warranty	20-Year Commercial Warranty	

PERFORMANCE

		TEST	REQUIREMENTS	RESULT
Supplementary* ASTM F 1700	Thickness	ASTM F 386	Nominal ± 0.0005 in.	Meets
	Size	ASTM F 2055	± 0.016 in. per linear foot	Pass
	Squareness	ASTM F 2055	0.010 in. max	Pass
	Residual Indentation	ASTM F 1914	Average < 8%	Pass
	Flexibility	ASTM F 137	≤ 1.0 in., no cracks or breaks	Pass
	Dimensional Stability	ASTM F 2199	0.02017 in. max.	Exceeds per linear foot
	Static Coefficient of Friction/Slip	ASTM D 2047	≥ 0.50	Pass
	Chemical Resistance	ASTM F 925	No more than slight change in surface dulling, attack or stain	Meets or Exceeds
	Resistance to Heat	ASTM F 1514	ΔE ≤ 8	Pass
	Resistance to Light	ASTM F 1515	ΔE ≤ 8	Pass
	Static Load Limit	ASTM F 970	No visually apparent indentation	250 psi
	Static Load Limit (Modified)	ASTM F 970 (MOD)	No visually apparent indentation	2,500 psi
	Fire Test Data – Flame Spread	ASTM E 648	0.45 watt/cm ² or more Class I	Meets
	Fire Test Data – Smoke Evolution	ASTM E 662	≤ 450	Meets
	Certified Low Emitting Product	LEED EQ4.3	-	Meets Guidelines
	Certified Low Emitting Adhesive	LEED EQ4.1	-	Meets Guidelines
	Indoor Air Quality	FloorScore [®]	-	Meets Guidelines
	Indoor Air Quality - Adhesives	FloorScore [®]	-	Meets Guidelines
	Indoor Air Quality	CHPS 01350	-	Meets Guidelines

*Exceptions may apply.











SIZE AND PACKAGING (size is dependent on design)

Tile Sizes	12 in. x 24 in. • 18 pieces/carton • 36 sq. ft./carton • 42 lb./carton 18 in. x 18 in. • 16 pieces/carton • 36 sq. ft./carton • 42 lb./carton 18 in. x 36 in. • 8 pieces/carton • 36 sq. ft./carton • 42 lb./carton
	4 in. x 36 in. • 36 pieces/carton • 36 sq. ft./carton • 42 lb./carton
Plank Sizes	6 in. x 36 in. • 24 pieces/carton • 36 sq. ft./carton • 42 lb./carton
	7.25 in. x 48 in. • 16 pieces/carton • 38 sq. ft./carton • 45 lb./carton
Shipping Weight	Contact Customer Service: 888.338.1029 or info@parterreflooring.com

TECHNICAL INFORMATION

For sustainability and adhesives information, warranties, installation and maintenance instructions, contact your Parterre Sales Representative or visit our website at: parterreflooring.com/resources

parterreflooring.com 888.338.1029 978.203.5400 version 6.12.2019